

Safety Data Sheet

DELETE Pattex SiliconeSani Tran

Page 1 of 9

SDS No.: 519593

V001.0

Date of issue: 13.01.2017

Cardiovascular system

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: DELETE Pattex SiliconeSani Tran

Intended use: Sealant

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137

Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u> <u>Hazard Category</u> <u>Target organ</u>

Serious eye irritation Category 2A
Skin sensitizer Category 1
Target Organ Systemic Toxicant - Category 2
Repeated exposure

Acute hazards to the aquatic Category 3 environment

Chronic hazards to the aquatic Category 3

environment

Hazard pictogram:



Signal word: Warning

SDS No.: 519593 V001.0

DELETE Pattex SiliconeSani Tran

Hazard statement(s): H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention: P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Distillates (petroleum), hydrotreated middle	64742-46-7	10- 30 %
Butan-2-one O,O',O"-(methylsilylidyne)trioxime	22984-54-9	10- 30 %
Butan-2-one O,O',O"-(vinylsilylidyne)trioxime	2224-33-1	< 1 %
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	< 1 %
non hazardous ingredients~		60- 100 %

Section 4. First aid measures

Ingestion: Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

Skin: In case of contact, immediately remove contaminated clothing and flush skin with copious

amounts of water. Seek medical advice.

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

DELETE Pattex SiliconeSani Tran V001.0

Inhalation. Move to fresh air.

Keep warm and in a quiet place.

Seek medical advice.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Decomposition products in case of

fire::

Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Oxides of nitrogen.

Silica fume

Thermal decomposition of this product may release formaldehyde which is a carcinogen.

Special protective equipment for

fire-fighters:

Wear full protective clothing.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes.

> Ensure adequate ventilation. Wear protective equipment.

Environmental precautions: Do not let product enter drains.

Clean-up methods: Scrape up as much material as possible.

Ensure adequate ventilation.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling: Ensure that workrooms are adequately ventilated.

Avoid contact with eyes, skin and clothing.

Wear suitable protective clothing, safety glasses and gloves.

Conditions for safe storage: Keep container tightly sealed.

Do not store or use near heat, spark, open flame or other sources of ignition.

Store in a cool, well-ventilated place.

< + 30 °C

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
OIL MIST, REFINED MINERAL 64742-46-7	Mist.		5	-	-	-	-

SDS No.: 519593 Page 4 of 9

V001.0 DELETE Pattex SiliconeSani Tran

Engineering controls: Ensure good ventilation/extraction.

Eye protection: For eye protection, use tightly fitted safety goggles and a face-shield

Skin protection: Wear suitable protective clothing.

Suitable protective gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: Neutral

Smooth Mild

Odor: Mild Specific gravity: 0.985

Flash point: > 100 °C (> 212 °F)
Density: 0.985 g/cm3
Solubility in water: Insoluble

Section 10. Stability and reactivity

Stability: Stable under recommended storage conditions.

Conditions to avoid: Avoid excessive heat and ignition sources.

Moisture.

Incompatible materials: Strong oxidizing agents.

Polymerises in presence of water. Reaction with strong acids. Reaction with strong bases

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide. Carbon dioxide. Oxides of nitrogen.

At higher temperatures (>150C) may release formaldehyde (traces).

Section 11. Toxicological information

SDS No.: 519593 V001.0

DELETE Pattex SiliconeSani Tran

Health Effects:

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin: May cause mild skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause skin sensitization.

Eyes: Causes serious eye irritation.

Symptoms may include severe irritation, pain, tearing, blurred vision.

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Butan-2-one O,O',O"-	LD50	2,463 mg/kg	oral		rat	OECD Guideline 401 (Acute
(methylsilylidyne)trioxim	LD50	> 2,000 mg/kg			rat	Oral Toxicity)
e			dermal			OECD Guideline 402 (Acute
22984-54-9						Dermal Toxicity)
Butan-2-one O,O',O"-	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 425 (Acute
(vinylsilylidyne)trioxime	LD50	> 2,009 mg/kg			rat	Oral Toxicity: Up-and-Down
2224-33-1			dermal			Procedure)
						OECD Guideline 402 (Acute
						Dermal Toxicity)
N-(3-	LD50	2,295 mg/kg	oral		rat	EPA OPPTS 870.1100 (Acute
(Trimethoxysilyl)propyl)e	LC50	1.49 - 2.44 mg/l	inhalation	4 h	rat	Oral Toxicity)
thylenediamine	LD50	> 2,000 mg/kg	dermal		rat	EPA OPPTS 870.1300 (Acute
1760-24-3						inhalation toxicity)
						EPA OPPTS 870.1200 (Acute
						Dermal Toxicity)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Butan-2-one O,O',O"-	irritating		rabbit	OECD Guideline 405 (Acute
(methylsilylidyne)trioxim				Eye Irritation / Corrosion)
e				
22984-54-9				
N-(3-	highly irritating		rabbit	OECD Guideline 405 (Acute
(Trimethoxysilyl)propyl)e				Eye Irritation / Corrosion)
thylenediamine				
1760-24-3				

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Butan-2-one O,O',O''- (methylsilylidyne)trioxim e 22984-54-9	Sensitizing	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	Sensitizing	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	sensitising	Mouse local lymphnod e assay (LLNA)	guinea pig	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Page 6 of 9 SDS No.: 519593 DELETE Pattex SiliconeSani Tran

V001.0

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	NOAEL=10 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

DELETE Pattex SiliconeSani Tran

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
C115 110.	ty pe		Study	time		
Butan-2-one O,O',O"- (methylsilylidyne)trioxime	LC50	> 560 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute
22984-54-9 Butan-2-one O,O',O"- (methylsilylidyne)trioxime 22984-54-9	EC50	> 750 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute
2230.0.7						Immobilisation Test)
Butan-2-one O,O',O"- (methylsilylidyne)trioxime 22984-54-9	EC50	94 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butan-2-one O,O',O"- (methylsilylidyne)trioxime	NOEC	30 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella	OECD Guideline
22984-54-9 Butan-2-one O,O',O"- (vinylsilylidyne)trioxime	LC50	> 560 mg/l	Fish	96 h	subcapitata) Brachydanio rerio (new name: Danio rerio)	Inhibition Test) OECD Guideline 203 (Fish, Acute
2224-33-1 Butan-2-one O,O',O"-	NOEC	50 mg/l	Fish	14 d	Oryzias latipes	Toxicity Test) OECD Guideline
(vinylsilylidyne)trioxime 2224-33-1 Butan-2-one O.O',O"-	EC50	201 mg/l	Daphnia	48 h	Daphnia magna	204 (Fish, Prolonged Toxicity Test: 14-day Study) OECD Guideline
(vinylsilylidyne)trioxime 2224-33-1	EC30	201 mg/l	Бариша	46 11	Dapinna magna	202 (Daphnia sp. Acute Immobilisation
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	EC50	94 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	Test) OECD Guideline
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	NOEC	30 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine	LC50	168 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
1760-24-3 N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC50	87.4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine	EC50	8.8 mg/l	Algae	96 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine	NOEC	3.1 mg/l	Algae	96 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC 50	435 mg/l	Bacteria	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

Page 8 of 9

SDS No.: 519593 V001.0

DELETE Pattex SiliconeSani Tran

Butan-2-one O,O',O"- (methylsilylidyne)trioxime 22984-54-9	Not biodegradable.	readily	aerobic	26 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	Not biodegradable.	readily	aerobic	26 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3			aerobic	50 %	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Butan-2-one O,O',O"-	9.83					not specified
(methylsilylidyne)trioxime						
22984-54-9						
N-(3-	-1.67					not specified
(Trimethoxysilyl)propyl)ethyl						
enediamine						
1760-24-3						

Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code)

General information:

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

Section 15. Regulatory information

SUSMP Poisons Schedule None

AICS: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICS).

DELETE Pattex SiliconeSani Tran

V001.0

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

STEL - Short term exposure limit TWA - Time weighted average

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue: 30.04.2013

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.