

Revision Number: 001.4 Issue date: 01/10/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: 5 Minute Epoxy Resin IDH number:

 Product type:
 Epoxy resin

 Restriction of Use:
 None identified

 Region:
 United States

 Company address:
 Contact information:

 Henkel Corporation
 Telephone: +1 (860) 571-5100

 One Henkel Way
 MEDICAL EMERGENCY Phon

One Henkel Way

Rocky Hill, Connecticut 06067

MEDICAL EMERGÉNCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

1071291

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*

Phenyl glycidyl ether	122-60-1	0 - 1
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	90 - 100

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get

medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Keep individual calm. DO NOT induce vomiting unless directed to do so by

medical personnel. If symptoms develop and persist, get medical attention.

Symptoms: See Section 11.

Notes to physician:Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Closed containers may

rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways. Remove all sources of

ignition. Wear appropriate protective equipment and clothing during clean-up.

Prevent further leakage or spillage if safe to do so.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin and

clothing. Wash thoroughly after handling. Keep container closed.

Storage: Store in original container until ready to use. Keep in a cool, well ventilated

area away from heat, sparks and open flame. Keep container tightly closed

until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Phenyl glycidyl ether	0.1 ppm TWA (SKIN) (Dermal sensitization)	10 ppm (60 mg/m3) PEL	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Viscous, Liquid

Color: Clear
Odor: None
Odor threshold: Not available.

oH: 6 - 7

Vapor pressure: < 0.13 kPa (180 °C (356°F)) Supplier method

Boiling point/range: $> 260.2 \,^{\circ}\text{C} \, (> 500.4 \,^{\circ}\text{F})$

Melting point/ range:
Specific gravity:

Not available.
1.04

Vapor density:

Flash point:

Not available.
> 150 °C (> 3

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Flammability:

Fvaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not available.

Not available.

Not available.

Not available.

VOC content: 0.1 % (value for resin and hardener together)

Viscosity: Not available.

Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

None

Incompatible materials: Strong acids. Strong oxidizing agents. Halogenated compounds. Strong mineral acids.

Reactive metals. Sodium hypochlorite. Calcium hypochlorite. Nitrous acid and other nitrosating

agents.

Reactivity: Not available.

Conditions to avoid: Excessive heat. Store away from incompatible materials.

IDH number: 1071291 Product name: 5 Minute Epoxy Resin

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Mild respiratory tract irritation.

Skin contact: Allergic skin reaction. Moderate skin irritation.

Eye contact: Moderate eye irritation. Redness.

Ingestion: Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Phenyl glycidyl ether	Oral LD50 (Rat) = 2.5 g/kg Oral LD50 (Mouse) = 1,400 mg/kg Dermal LD50 (Rabbit) = 1,500 mg/kg Inhalation LC50 (Mouse, 4 h) = > 100 mg/l	Allergen, Blood, Bone Marrow, Central nervous system, Immune system, Irritant, Reproductive, Respiratory, Some evidence of carcinogenicity	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Phenyl glycidyl ether	No	Group 2B	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin

resin)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

IDH number: 1071291 Product name: 5 Minute Epoxy Resin

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A

Epichlorhydrin resin)

Hazard class or division: 9
Identification number: U

Identification number: UN 3082 Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Immediate Health, Delayed Health
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 3

Prepared by: Donna Houston, Regulatory Affairs Specialist

Issue date: 01/10/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1071291 Product name: 5 Minute Epoxy Resin