



**DECLARATION OF PERFORMANCE
according to Annex III of the Regulation (EU) No 305/2011**

Name of the product: **Ceresit Easy Fix**

No 00096A

1. Unique identification code of the product-type: **EN 12004 – D2TE**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Improved dispersion adhesive with reduced slip and extended open time
for internal wall tiling**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required to Article 11(5):

**Henkel Limited, Technologies House, Wood Lane End, Hemel Hempstead
HP2 4RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory **NB 1289**, performed the determination of the product-type on the basis of the type testing under system 3 and issued a test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Bond strength as		EN 12004:2007+A1:2012
Initial shear adhesion strength	$\geq 1 \text{ N/mm}^2$	
Durability of bond strength as:		
Shear adhesion strength after heat ageing	$\geq 1 \text{ N/mm}^2$	
Shear adhesion strength after water immersion	$\geq 0.5 \text{ N/mm}^2$	
Shear adhesion strength at elevated temperatures	$\geq 1 \text{ N/mm}^2$	
Open time: Tensile adhesion strength after not less than 30 min.	$\geq 0.5 \text{ N/mm}^2$	
Slip	$\leq 0.5 \text{ mm}$	
Reaction to fire	Class F	
Release of dangerous substances	See MSDS	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Head of Product Development &
Technical Services
Paul Barney

Plant Manager
Graham Newton

Winsford, 05/02/18
