



TECHNICAL DATA SHEET



Henkel Canada Corporation
Professional and Consumer Adhesives
Mississauga, ON L5N 6C3
Phone 1-800-624-7767
Fax (440) 250-9661
www.henkel.com www.lepage.com

DESCRIPTION

LePage® Polyfilla® Wall Paint Preparation is a ready to use, extra fine patching compound for repairing surface damage to interior walls. Ideal for smoothing surface imperfections and filling shallow cracks and holes. The creamy, off-white paste spreads easily, dries fast and sands to a super fine finish that is smooth, hard and dent resistant. It has low odour and wet filler can be easily cleaned with water. Polyfilla® Wall Paint Preparation is also paintable and sandable once fully dry.

RECOMMENDED FOR:

- Use on interior wood, drywall, wallboard and plaster.
- Fills shallow cracks and holes, smoothes wood grain, covers hammer marks and fills over nail and screw heads.

NOT RECOMMENDED FOR:

- Exterior applications
- Areas in contact with moisture or water
- Filling large, deep holes
- Repairs subject to movement or requiring flexibility

FEATURES & BENEFITS:

Feature	Benefits
Ready to use.....	No mixing required
Paintable and sandable.....	Blends with surroundings
Quick drying.....	Rapid completion of repairs
Non-sagging.....	Easy to apply
Water clean-up.....	No harsh cleaning chemicals required



Item #	Package	Size
1256102	Plastic Tub	300 mL
1256105	Plastic Tub	900 mL
1292879	Plastic Pail	2.7 L

DIRECTIONS

Tools Typically Required:

Spatula or putty knife, 80 and 120 grit sandpaper.

Safety Precautions:

Wash hands after use.

Preparation:

Apply and cure product above 10°C (50°F). Colder temperatures and humid conditions will greatly extend drying time. Surfaces must be clean, dry and free of loose materials. Remove ragged drywall paper from damaged edges.

Application:

Apply with a spatula or putty knife and smooth. For best results, fill slightly above the surface level and overlap onto the surrounding area. For filling deeper holes and depressions, avoid cracking due to shrinkage by applying in layers 2 to 3 mm (1/16 to 1/8") thick. Allow each layer to dry before applying the next. Allow Poly Filla® Wall Paint Preparation to dry and then sand into the surrounding surfaces using an 80 grit paper and finishing with a 120 grit paper. Prime filled area before painting. The patch can be painted with a water-based or oil-based paint. If not completely dry, the paint may bubble or lift.

Clean-up:

Clean hands and tools immediately with water. Cured filler may be sanded.

STORAGE AND DISPOSAL

DAMAGED BY FREEZING. Store tightly sealed to prevent drying. Product should not be washed down drain to avoid clogging. To dispose of unwanted product, scrape out from tub, allow to harden and discard with trash. Wipe/rinse container and place with plastics for recycling.

PRECAUTIONS

Keep out of the reach of children.

Refer to the Material Safety Data Sheet (MSDS) for further information.

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

TECHNICAL DATA

Typical Uncured Physical Properties		Typical Application Properties	
-------------------------------------	--	--------------------------------	--

<u>Colour:</u>	Off-white	<u>Application Temperature:</u>	Apply and cure above 10°C (50°F)
<u>Appearance:</u>	Smooth, buttery paste	<u>Odour:</u>	Low
<u>Base:</u>	Polymer binder / natural limestone and other fillers	<u>Clean up:</u>	Water cleanup for wet material.
<u>pH:</u>	7.3	<u>Dry Time:</u>	Varies with application thickness, temperature And humidity. A 2 to 3 mm (1/16" to 1/8") depth hole dries in approximately 4 hours.
<u>Specific Gravity:</u>	1.55		
<u>% Solids:</u>	76.5 %		
<u>Viscosity:</u>	1200 Mcps @ 1 rpm		
<u>Shelf Life:</u>	18 months from date of manufacture (unopened)		

Lot Code Explanation: YM123
 Y= Year
 M = Month
 123 = The batch # of a product manufactured in that given month and year.

(Lot code is stamped on the bottom of the tubs)

For example:
 CM028
 C = Year = 2013
 M = Month = November
 028 = This is the 28th batch of this product to be manufactured in Nov. 2013.

Year		Month	
2006	F	January	A
2007	G	February	B
2008	H	March	C
2009	J	April	D
2010	K	May	E
2011	A	June	F
2012	B	July	G
2013	C	August	H
2014	D	September	J
2015	E	October	K
2016	F	November	M
2017	G	December	N

Note: I, L and O have been skipped so as not to confuse the letters with numbers.

Typical Cured Performance Properties

<u>Colour:</u>	Off-white	<u>Sandable:</u>	Yes
<u>Cured Form:</u>	Hard solid	<u>Paintable:</u>	Yes
<u>Water Resistant:</u>	No, for interior use only.	<u>Clean up:</u>	Sand or scrape away dried material.