



Excellence is our Passion

# Technical Data Sheet – Master File

Technical Data Sheet  
Revision: 1  
Issued: 02.05.2018  
Number of pages: 2

## Pritt wood and craft glue

EAN code: [6001091351655]

Solvent-free White Glue, based on PVA-Dispersion



### CHARACTERISTICS

- Water-based polyvinyl acetate glue for crafting and hobby
- Color white, dried film transparent
- CE conform according to EN 71
- solvent-free
- Washable at 20°C
- Easy application bottle: dots, line or larger surface with thin film
- Suitable wood, bast, cork, leather, Styropor®, felt, fabrics, cardboard, paper and a lot more (no plastics).

### APPLICATION FIELD

Adhesive for home, school and office. Ideal for crafting.

### INSTRUCTIONS FOR USE

#### Pretreatment

Clean the material surface before gluing. Best bonding strength will be achieved if surface is dry and free from dust and grease. (Rub and wipe with a cleaning solution e.g. white spirit). Very smooth surfaces should be roughened with sand paper. Remove oxide layers of metals, e.g. aluminium, before gluing.

#### Application

Apply a thin layer of Pritt craft glue onto one side, join and fix the pieces together.

For porous materials (e.g. wood, cardboard): apply Pritt craft glue on both surfaces to be bonded and join them. A correction of the bonded materials is possible. (Setting time = approx. 60 min; depends on ambient temperature, moisture content and thickness of the materials).

Close cap tightly after use!

The maximum bonding strength is reached after 24 hours.

### TECHNICAL DATA



Excellence is our Passion

Composition	Polyvinyl acetate dispersion
Density	ca. 1.1 g/cm <sup>3</sup> .
pH	5,5 – 7,0
Solid content	38 -40%
Viscosity: (5/20°C/20 rpm)	> 8000 mPas
Shelf Life	12 months at 20 °C

## LIMITATIONS

### Storage

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and over 50°C.

## HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

**Henkel South Africa (Pty) Ltd**  
55 Potgieter Road, Alrode, Gauteng  
Toll Free Number: 0800 13 81 81  
Internet: [www.prittworld.com](http://www.prittworld.com)