

Technical Data Sheet - Master File

Technical Data Sheet

Revision: 2

Issued: 29.11.2018 Number of pages: 2







Pritt Stick

11g, 22g & 43g

EAN code:

11g: 6001091349249 22g: 6001091349256 43g: 6001091349263

Solvent-free glue stick (11g, 22g, 43g)

CHARACTERISTICS

- Water-based glue stick for crafting and hobby
- CE conform according to EN 71
- Solvent-free
- > Acid-free, suitable for archiving
- > 90% natural ingredients (incl. water)*
- Washable at 20°C
- Easy application
- ➤ High efficiency*
- Suitable for cardboard, paper, felt, cork, photos and paper stickers

^{*)} confirmed by Fraunhofer – Institut für Fertigungstechnik und Angewandte Materialforschung (IFAM)



APPLICATION FIELD

Glue stick adhesive for home, kindergarten, school and office. Ideal for crafting and hobby.

INSTRUCTIONS FOR USE

Pretreatment

Not necessary. In general, surfaces have to be clean, dry and free of dust and grease.

Application

Apply the adhesive two or three times on the surface and join the bonding parts together. Close the cap properly after use to avoid drying out of the glue mass. Correction of the bonding parts is possible within a short time after bonding.

Close cap tightly after use!

TECHNICAL DATA

Composition	Polyglycoside ether,
	polysaccharides, soap
	and water
pH	10,0-10,2
Open time**	up to 210 sec
Setting time**	60 - 90 sec
color	white
Shelf Life	36 months at 20 °C

^{**)} parameter depends on ambient temperature, moisture content and thickness (characteristic) of the materials.

LIMITATIONS

Storage

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and over 50°C.



HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel South Africa (Pty) Ltd

55 Potgieter Street, Alrode, Ext. 4, Alberton, 1451

Phone: +27 (0) 11 617 2400 Internet: www.prittworld.co.za