



Technical Data Sheet



Technical Data Sheet
Ref: NRLO19000TDS
Issued: 02.04.20
Number of pages: 02

Loctite Super Glue Power Easy

CHARACTERISTICS

LOCTITE® Power Easy is a one-part fast setting adhesive. It is designed for home use and forms strong bonds between a wide range of common materials. It is the ideal adhesive for bonding materials such as plastics*, rubbers, metals, woods, ceramics, leather, fabrics, cardboard and paper.

LOCTITE® Power Easy is low-odour and slower than standard Super Glue, making it repositionable and slower to bond skin (at least twice as long compared to LOCTITE® Super Glue).

Bonding Speed: Initial adhesion in 15 to 120 seconds, depending on the substrate.

Bond Strengths (ISO 4587): 10 to 20 N/mm² (tensile shear) in 12 to 24 hours, depending on the substrate.

INSTRUCTIONS FOR USE

1. Ensure all surfaces to be bonded are clean and dry and close-fitting.
2. Avoid skin contact with the glue.
3. Apply a minimum quantity of LOCTITE® Power Easy to one of the surfaces to be bonded.
4. Bring parts together immediately and hold by hand pressure for at least 1 minute.
5. Leave undisturbed for 30 minutes or preferably overnight to allow full bond strength to develop.
6. Avoid spillages and protect work surfaces. Remove cured residues of Power Easy with LOCTITE® Super Glue Remover.
7. For best results, the bonds should be prepared at room temperature (15-30°C) and a minimum 30% relative humidity.
8. For optimum product life, wipe the nozzle with a tissue to remove excess adhesive, replace cap and store the pack in a cool, dry place.





TECHNICAL DATA

Composition	β -Methoxyethyl cyanoacrylate
Appearance	Clear
Density	1.1 g/cm ³ @ 20 °C
Viscosity @ 25 °C	~ 2000 mPa.s
Pack	3g tube
Safety	See Safety Data Sheet
Shelf Life at 20 °C	18 months, unopened, from date of production

LIMITATIONS

- For indoor use only
- Do not use on dusty, dirty or wet surfaces
- *Not suitable for bonding waxy or soft plastics, e.g. PP, PE, Teflon® (PFTE), vinyl
- Not suitable for silicone rubber, expanded polystyrene, foams, glass, synthetic fabric
- Leather: test on hidden area first
- Not suitable for permanently wet areas
- Not suitable for bonding silicone rubber, glass, glazed surfaces, very soft leather or foams
- Never use for bonding assemblies that will hold hot liquids
- Optimum bonding performance is achieved in dry conditions

STORAGE

Store in a cool, dry place, out of reach of children.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Norden AB

Box 151 22
Gustavslundsvägen 151A
SE-167 15 Bromma, Sweden