



Technical Data Sheet



Technical Data Sheet
Ref: PR1000
Issued: 27.07.2017
Number of pages: 2

Pritt Refill Glue Roller Permanent & Non-Permanent

PRODUCT DESCRIPTION:

Pritt Refill Glue Roller Permanent & Non-Permanent for easy and precise gluing jobs. The roller is available with a permanent strong adhesive tape, red coloured refill cassette and tape or with a non-permanent repositionable adhesive tape, yellow coloured refill cassette and tape. The roller has a protective cap.



TECHNICAL PRODUCT DESCRIPTION:

Injection moulded plastic parts

- Refill cassette is made out of up to 50% of recycled plastic and 100% recyclable

Tape

- Siliconized polyester layer combined with a polyacrylate based adhesive



CHARACTERISTICS:

- Clean and precise application (no more stringing) thank to the new honeycomb tape
- Bonds cleanly, quickly and precisely
- Permanent - bonds permanently to various 2 dimensional materials such as paper, cardboard, photos.
- Repositionable - bonds repositionably to various 2 dimensional materials like paper, cardboard.
- Glue film does not dry out and is always ready for instant use
- Strong non tearable band (PET)
- Visible bond line due to coloured adhesive layer
- Solvent free

INSTRUCTIONS FOR USE:

Place paper/material to be glued on a smooth, flat and steady surface.

Position the roller – printed side up – at a 30° angle and place it at the furthest gluing point. Apply a light, but firm pressure on the roller nib and draw the roller back over the surface you wish to glue. Make sure of putting the application roll flat on the surface at every application. For a clean break, stop and lift up at a slight angle.

For the repositionable roller always apply the adhesive to the disposable item, as the adhesive sticks permanently on the material to which it is first applied.

TECHNICAL DATA

Tape length	16m
Tape width	8.4mm
Shelf Life	2 years

Storage at room temperature and dry

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

Henkel Limited

Road 5, Winsford Industrial Estate, Winsford, Cheshire, CW7 3QY

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

e.mail: technical.services@henkel.co.uk