



# **Technical Data Sheet**

Technical Data Sheet Revision: 1 Issued:24.05.2018 Number of pages:2

## Pritt Project Glue EAN code: [6001091348693]

## PRODUCT DESCRIPTION:

Pritt Project Glue is a synthetic resin emulsion, which has many different uses in the home. The bonds produced are flexible and have a clear glue line.

#### **TECHNICAL PRODUCT DESCRIPTION:**

#### Application

Pritt Project Glue can be used to bond the following:

- paper, cardboard
- fabric
- leather

• Pritt Project Glue is ideal for use on polystyrene Not recommended for polyethylene, polypropylene, Teflon or applications that require resistant to heat or moisture.

### **TECHNICAL DATA**

viscosity:	brushable, approx. 4 500 mPa.s at 20 °C
total solids:	approx. 52%
density:	approx. 1.1 at 25 °C



#### **INSTRUCTIONS FOR USE:**

Apply to one surface, clamp together, and allow the adhesive

to dry. The drying time will depend on the porosity of the substrates, the ambient temperature and relative humidity

#### Clean up.

Spillage's can be cleaned with water when wet, dry deposits can be soaked in warm water and scraped clean.



#### Storage

Store in a cool, dry place. Optimum storage temperatures are between 15 and 25 °C. Do not store in direct sunlight and protect from freezing. Strict batch rotation must be observed.

## Shelf life

The life of an unopened container, stored correctly, is 12 months.

#### Health and Safety data

Pritt Project Glue is solvent free and non-toxic. This adhesive presents no fire hazard. Do not swallow.

#### Pack sizes available.

50 ml tube 120 ml bottle

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

#### Henkel South Africa (Pty) Ltd

55 Potgieter Road, Alrode, Gauteng Toll Free Number: 0800 13 81 81 Internet: www.prittworld.com