



# Technical Data Sheet



Technical Data Sheet  
Revision: 1  
Issued: 02.05.2018  
Number of pages: 2

## Pritt Clear Glue

EAN code: [6001091350498]

### PRODUCT DESCRIPTION:

Pritt Compact Flex Correction Roller for easy and precise correction jobs. The roller is available in two different width 4,2mm & 6,0mm for machine or hand-written text and with protective cap. Smooth and clean application thanks to new flexible nip. The corrected area can be overwritten without any drying time. The optimised correction layer shows outstanding smear resistance and coverage properties.

### TECHNICAL PRODUCT DESCRIPTION:

#### Injection moulded plastic parts

➤ The Pritt Compact Flex Correction Roller is made from up to 50% recycled plastic and 100% recyclable

#### Tape

- Siliconised polyester carrier
- Synthetic resin with titan dioxide, cover up layer combined with a polyacrylate based adhesive

### CHARACTERISTICS:

- Premium correction tape for instant rewriting
- The roller head produces smooth consistent corrections.
- The flexible head applies tape firmly to the paper while allowing manoeuvrability for detailed Corrections
- Push and pull function
- Immediate coverage of nearly all types of writing, prints and drawings
- Good adhesion on smooth and nearly smooth surfaces
- Cover up layer needs no drying time and can be overwritten with all common inks, pens and machines
- No smearing of water based inks on the cover up layer while overwriting
- No shadows on copies
- Writing tips or printing heads will not be damaged when applied correctly
- Solvent free





## INSTRUCTIONS FOR USE:

Place paper/material to be corrected on a smooth, flat and steady surface.

Position the roller – printed side up – at a 30 - 60° angle and place it at the furthest correction point. Apply a light, but firm pressure on the roller nib and draw the roller back over the surface you wish to correct. Make sure of putting the application roll flat on the surface at every application. For a clean break, stop and lift up at a slight angle.

Push and Pull function: Pushing works well when you want to correct single letter. Pulling is best for longer corrections, such as full sentences.

If the cover up layer should not stick properly to the paper, i.e. on critical coated papers the film may be finished with light pressure with your finger.

## TECHNICAL DATA

Viscosity	10m
Total solids	4,2mm & 6,0mm
Density (SG)	
Drying time	
Shelf Life	12 months

**Storage at room temperature and dry**

## HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

**Henkel South Africa (Pty) Ltd**  
55 Potgieter Road, Alrode, Gauteng  
Toll Free Number: 0800 13 81 81  
Internet: [www.prittworld.com](http://www.prittworld.com)