

Technical Data Sheet

Pritt Stick (43g + Free Multitack 20g) x 24

EAN code: [6001091351723]

Solvent-free glue stick (43g)



Technical Data Sheet
Revision: 1
Issued: 17.04.2018
Number of pages: 3

CHARACTERISTICS

- Water-based glue stick for crafting and hobby
- CE conform according to EN 71
- Solvent-free
- Acid-free suitable for archiving
- 90% renewable ingredients (incl. water)
- Washable at 20°C
- Easy application
- High initial tack*
- High efficiency*
- Suitable for cardboard, paper, felt, cork, photos and paper stickers

confirmed by Fraunhofer – Institut für Fertigungstechnik und Angewandte Materialforschung (IFAM)
(Institute for manufacturing engineering and applied materials research)

APPLICATION FIELD

Glue stick adhesive for home, kindergarten, school and office. Ideal for crafting and hobby.

INSTRUCTIONS FOR USE

Pretreatment

Not necessary. In general, surfaces must be clean, dry and free of dust and grease.

Application

Apply the adhesive two or three times on the surface and join the bonding parts together.

Close the cap properly after use to avoid drying out of the glue mass.

Correction of the bonding parts is possible within a short time after bonding.

Close cap tightly after use! * parameter depends on ambient temperature, moisture content and thickness (characteristic) of the materials.

The maximum bonding strength is reached after 24 hours.

Close cap tightly after use

TECHNICAL DATA

Composition	Polyglycoside ether, polysaccharides, soap and water
pH	10,0 – 10,2
Open time**	up to 210 seconds
color	White
Shelf Life	36 months at 20 °C

parameter depends on ambient temperature, moisture content and thickness (characteristic) of the materials.

LIMITATIONS

Storage

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and over 50°C.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.



Excellence is our Passion

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

Henkel South Africa (Pty) Ltd.

55 Potgieter Street, Alrode, Ext 4, Gauteng

Phone: +27 11 617-2400

Internet: www.prittworld.co.za