

## PATTEX EPOXY UNIVERSAL 5 MIN SYRINGE 11ML

### DESCRIPTION

**Pattex Epoxy Mini Syringe** is a fast setting, gap filling, two-part adhesive which produces rigid bonds with high bond strengths. The glue line is resistant to water and most common solvents. It gives you the high bonding performance you need for almost any material and repair. It dries very fast and transparently and won't expand or shrink when curing. It can be used both outdoors and indoors and you can paint, sand, polish and even drill it.

IDH	Packaging type	Size
2753928	Syringe	12g

### CHARACTERISTICS

- Extremely strong bonding
- Convenient instant mix syringe
- Water and temperature resistant
- Indoor & Outdoor use
- Invisible Repairs

### APPLICATION

**Pattex Epoxy Mini Syringe** can be used to bond the following:

- Wood
- Glass
- Ceramics
- Metals

The bond formed can be cut, sanded or planed when fully cured.



## TECHNICAL DATA

Mixing ratio	1:1 by volume
Pot life	5 minutes
Initial Cure	2 hours @ 25°c
Final cure	24 hours
Temperature resistance	-20 - 120 °c, depending on duration of exposure to heat and stress
Shear strength	10 – 13 n/mm <sup>2</sup> (steel / steel)
Pattex Epoxy volume/ amount information:	11ml epoxy, component A&B is 5.5ml each. Weight of A:5.5x1.16=6.38g, B:5.5x1.1=6.05G

## DIRECTIONS FOR USE

- For optimum results, use the adhesive between 15°C and 30°C. The cure rate is retarded by low temperatures and accelerated at higher temperatures.
- The surface to be filled must be clean, free of dust and grease.
- Mix equal volumes of resin and hardener thoroughly.
- Apply a thin film of mixed adhesive to both surfaces. Join the two parts immediately and clamp in place. The assembly can be handled after 30 minutes.
- Remove excess adhesive with a sharp blade or knife.
- Take care to replace the caps onto the correct tubes.

## CLEAN UP

Spillages can be cleaned with acetone or Tangit Cleaner before the adhesive has cured. Care must be taken when using these solvents as they are flammable and may cause damage to certain surfaces.

## STORAGE

Store in a cool, dry place.

## SHELF LIFE

18 months in unopened container, if stored correctly.

## HEALTH AND SAFETY DATA

Wash hands with warm soapy water after working with Pattex Epoxy Mini Syringe. Wear gloves in cases of prolonged exposure to this adhesive. Refer to Material Data Sheet.

## LIMITATIONS

The information provided herein, especially recommendations for the use and application of our products, is based upon our current knowledge and experience. Due to different possible applications as well as varying application and working conditions, which are beyond our control, we strongly recommend carrying out sufficient extensive prior trials to confirm the suitability of our products for the relevant production processes, as well as the intended applications and results. Any liability in respect of the information in this Technical Data Sheet or any oral recommendations is excluded, except in the event of harm to life, physical injury or harm to health or if we are liable for gross negligence or willful misconduct or according to applicable mandatory product liability law.