



Technical Data Sheet



Pattex Multi-Purpose Contact Adhesive Liquid

Technical Data Sheet
Ref: NRPTX7000TDS
Issued: 09.04.20
Number of pages: 3



CHARACTERISTICS

- Fast drying, liquid multi-purpose contact adhesive
- Ideal for fast repairs to horizontal surfaces
- Bonds most materials without clamping
- Flexible
- High initial and final strength
- High heat resistance
- Resistant to ageing

APPLICATION FIELD

Pattex Multi-Purpose Contact Adhesive Liquid is suitable for bonding decorative laminates and veneer strips, wood, MDF, metal, cork, leather, rubber, rigid PVC, soft foams, ceramics, stone.

INSTRUCTIONS FOR USE

Preparation

Surfaces must be close fitting, clean, dry and free from dust, grease or paint. Coated or treated surfaces should be stripped and cleaned beforehand.

Important: Clean laminates, metal etc. with white sprit and allow to dry before applying adhesive. Abrasion of surfaces to be bonded will increase bond strength. Allow materials to acclimatise according to manufacturer's instructions before bonding.

Application

1. Apply a thin, even coat of adhesive to both surfaces, especially at the edges, using a serrated spreader or clean, short bristled brush. Ensure the entire surface to be bonded is covered. For best results apply adhesive at temperature of +18°C to +25°C



2. Allow the adhesive to dry for approx. 15 minutes until touch dry (the adhesive film must not stick to the finger or be "stringy"). After evaporation of the solvents there must be an unbroken, visible film of adhesive left on the surface. It may be necessary to apply several coats of adhesive to highly absorbent materials
3. Carefully align parts and press together. Apply firm pressure for a few seconds from the centre of the bonded area outwards, ensuring that any air bubbles are pressed out. Press carefully on edges. Use a rubber roller on large surface areas such as laminate panels. **Important:** Bonding will be instant and not repositionable

TECHNICAL DATA

Composition	Solvent based polychloroprene rubber
Density	0.86 g/cm ³
Heat resistance	- 40°C up to 110°C
Application temperature	Pattex Multi-Purpose Contact Adhesive Liquid should preferably be used at temperature of +18°C to +25°C
Coverage	250-350 g/m ²
Final strength (EN 205)	1 to 3 days depending on surface area and pressure applied
Shelf Life	24 months when stored in cool, dry conditions, protected from sunlight
Evaporation time	10-15 minutes at room temperature

LIMITATIONS

Not suitable for polyethylene (PE), polypropylene (PP), expanded polystyrene, synthetic leather and plasticized PVC.

Adhesive should be applied used on flat, horizontal surfaces.

Not suitable for areas of constant immersion or permanent damp.

Cleaning tools

Clean tools immediately after use with white spirit.

Storage

Store tightly closed and at room temperature. Avoid temperatures lower +5°C and above +50°C.

Cold or frozen adhesive (under + 5°C) will become fully usable again if slowly acclimatized up to working temperature (approx. +20°C). No loss of quality is suffered. During work pauses the adhesive container should be kept tightly closed to prevent evaporation of the solvents.

PACKAGING

50g aluminium tube
4.5kg tin



HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Norden AB

Box 151 22
Gustavslundsvägen 151A
SE-167 15 Bromma, Sweden