



Technical Data Sheet



Technical Data Sheet
Ref: NRPTX72000
Issued: 20.04.21
Number of pages: 4

Pattex No More Nails All Materials Quick Drying



CHARACTERISTICS

- Flextec polymer based formula
 - Moisture-reactive curing
 - Flexible bonding
 - Fast build-up of strength
 - Handling strength after 20 minutes*
 - Instant Tack
 - Correctable for a few minutes
 - Interior and exterior use
 - Weather and aging resistant
 - Porous- and non-porous surfaces
 - Works on wet surfaces
 - Multiple materials
 - Sensitive materials
 - Gap-bridging
 - No stringing or dripping
 - No shrinkage
 - Easy application at low temperature
 - Isocyanate- free
 - Solvent- free
 - Phthalate-free
- * depending on substrate and application

APPLICATION FIELD

- Pattex No More Nails All Materials Quick Drying is multiple-substrate compatible including Brick, Ceramic, Concrete, Hardboard, Plasterboard, Plywood, Stone, MDF, Wood, Metal, UPVC, Glass, Plastics*, painted surfaces *, Mirrors**.

*Pre-test to determine suitable bonding, because of many different substrates.**Use mirrors acc. DIN EN 1036-1, ask for technical advise for large-scale objects.

- All absorbent and non-absorbent substrates except PE, PP, PTFE, acrylic glass, copper, brass, Styrofoam and plasticised PVC are suitable. With coated substrates, a check of product suitability or professional advice is recommended. Wet surfaces are possible if it has the possibility to dry. Not recommended for permanent water immersion.



INSTRUCTIONS FOR USE

Pretreatment


Ensure surfaces to be bonded are clean and free of dust, grease or oil. Pooled water on absorbent substrates should be first removed.

Substrates must be stable, clean and free from substances. Remove the soiling with the appropriate solvent or sand down surfaces and clean afterwards from dust. Before application, mask off the adjacent area with foil or tape, if necessary. Check paint or coatings are firmly attached, if not remove it.


Curing of the adhesive requires the intake of a small amount of moisture (either from the atmosphere and/or from the substrate).

Application

Cut off tip of the cartridge above the screw thread (1). Screw on plastic nozzle and diagonally cut off the tip of the nozzle (2). Place cartridge into gun (3).



Apply adhesive onto one of the surfaces: In spots (1) in order to smooth uneven surfaces, in wave-like form (2) for higher initial tack with wide surfaces or in straight strands for smaller surfaces (3). In case of outdoor use, apply **vertical** strands.



Release gun after appliance to stop adhesive from flowing (not valid for Foldable Gun (DW111)).

Ensure Ventilation. (1 mm Minimum gap)

Important in case of 2 non-absorbent surfaces: Adhesive must not form continuous areas as contact with air is necessary for adhesive setting. Then put the two surfaces together, correct if necessary, and press thoroughly. Make sure the adhesive tracks do not merge.

Heavy items and items under tension have to be supported and fixed for at least 24 hrs.

TECHNICAL DATA

Uncured material

Raw material	Silane cross-linking polymer (Flextec)
Density	Approx. 1,4 g/cm ³
Application temperature	+5°C up to +40°C
Open time	Approx. 5 Min
Initial tack	Approx. 10 g/cm ²
Curing Speed	2mm/24 h (23°C/50%r.h)
Gap bridging capacity	Up to 20 mm



Coverage on flat surfaces	Approx. 300 g/m ²
Shrinkage	No shrinkage
Shelf life	Cartridge: 12 months

Cured material

Heat resistance	-30°C up to +80°C, 100°C for short periods
Bond resistance	Weather, aging and moisture resistant
Final Strength (DIN EN 205)	3,0 - 3,5 N/mm ² <small>(lap-shear strength, Alu/Alu)</small>
Elongation at rupture (DIN 53504)	Approx. 200 - 250 %

LIMITATIONS

Cleaning

Clean directly after use with a dry cloth and afterwards with commercial thinners or cleaning petrol. Remove uncured spots of adhesive at once. The cured Pattex No More Nails All Materials Quick Drying is insoluble in all solvents and can only be removed mechanically with appropriate tool (scraper). Clean tools immediately after use with thinner or white spirit.

Do not use Pattex No More Nails All Materials Quick Drying as a sealant, on bituminous substrates or on building materials, which might bleed oils, plasticizer or solvents, which could attack the product.

Not suitable for applications with water pressure or permanent water immersion/constant damp, e.g. in swimming pools below the water line, water pipes.

Will not bond to PE, PP, PTFE, PMMA (Acrylic), plasticised PVC, copper and brass

Pattex No More Nails All Materials Quick Drying can only be over-painted with water based paint (Pre-test recommended to determine suitability).

Pre-test coated substrates to ensure suitability of use

Product may only be used for mirror bonding if the mirror coating and the protective lacquer complies with EN 1036-1. In case of unknown mirror qualities and large projects, please ask mirror producer for a recommendation.

Pattex No More Nails All Materials Quick Drying cannot be over painted

Storage

Store cool, dry and unopened. Once opened, be sure to recap, use entire cartridge shortly after opening. Store away from heat, flame, and spark in a cool, well ventilated area. Product is not damaged by freezing, but avoid big temperature-changing during storage. Keep away from children.



HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Norden AB

Box 151 22

Gustavslundsvägen 151A

SE-167 15 Bromma, Sweden