



Excellence is our Passion

Technical Data Sheet – Mounting Strips



Technical Data Sheet
Revision: 1
Issued: 31 July 2012
Number of pages: 3

Pattex NMN Removable Mounting Strips 2kg x 12

EAN code: 600 109 135 2461

Product description: double- sided foam mounting strips for removable mounting applications.

CHARACTERISTICS

Pattex Mounting Strips Removable is a double-sided die cut pad for removable mounting applications for interior and exterior use with excellent UV resistance.

- Easy – without additional tools
- Quite – without drill or drill noise
- Clean – without dirt and dust

APPLICATION FIELD

- Pattex Mounting Strips Removable can be used to fix objects on many different smooth surfaces like tiles, metal, wood, stone and many plastics*.
*not for the use on PE, PP, PTFE (Teflon)
- For inside and outside applications.
- Ideal for mounting applications of kitchen and bathroom accessories, household appliances, decoration objects, skirting boards, house numbers, etc.
- Not recommended for applications on delicate surfaces.

INSTRUCTIONS FOR USE

Application

Ensure surfaces to be bonded are clean and free of dust, grease or oil. Surfaces should be load-bearing (Clean surface with alcohol, cleaning benzene or acetone).

Apply tape without any air-bubbles on the substrate and remove yellow protection liner and press it afterwards hard on the ground where to bond.



Excellence is our Passion

Avoid application temperatures under 10 °C. Maximum holding power of 2,0kg per strip will be reached under ideal conditions: mounting of flat objects (thickness <10mm) to smooth glass or metal surfaces. Direct contact with water can reduce holding power. Final strength is reached after 24h.

For mounting of objects with a thickness >10mm, holding power per strip is reduced. To fix larger objects (thickness >10mm, weight >2kg) use more strips.

Distribute the strips homogeneous on the surface respecting a space of 3 - 5 cm between each strip.

On surfaces other than glass or metal, holding power per strip can be reduced.

How to Remove the Strips

Give the object a short, sharp turn (take care if removing breakable items such as glass, porcelain, china, etc.) or split the foam carrier with a thread.

After removing the object, remaining foam can be easily peeled off.

TECHNICAL DATA

Colour / Appearance	White foam / double-sided tape
Carrier material	Polyethylene foam
Adhesive	Acrylic
Liner	Yellow Polyethylene/Propylene
Width	20mm
Length	40mm
Gap bridging capacity	Max. 1,0mm
Temperature resistance	Up to 95°C (short term)
Processing temperature	10°C to 35°C
Shelf life	24 month

LIMITATIONS

Storage

Store in a dry, dust free place between 10 C° and 30 °C.

Important Remark

Delicate surfaces can be damaged when removing the tape. Pattex Mounting Strip Removable is **not recommended** for the use of silicon. Wallpaper (vinyl or paper) not load-bearing or dirt-repellent surfaces. In doubt the tape must be tested in an inconspicuous place.



Excellence is our Passion

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request

Disposal

Household waste

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel SA PTY Ltd

55 Potgieter Stree, Alrode Ext 4

Phone: +27 (0) 617 2400

Toll free No: 0800 138 181