

## Loctite® FUN-TAK® Mounting Putty



### DESCRIPTION

**Description:** Loctite® Fun-Tak® Mounting Putty is a reusable, removable adhesive that is a convenient alternative for tape, tacks, staples and magnets in the home, school, and office. No more holes in walls or chipped, peeled paint. Ideal for hanging any lightweight item to a smooth or hard surface. Loctite Fun-Tak Mounting Putty is unaffected by moisture and will not dry out. For interior use only.

#### Available As:

Item #	Package	Size
1865809	Carded Blister – Mounting Putty	2.0 ounce
1270884	Carded Blister – Mounting Putty Tabs	2.0 ounce

### FEATURES & BENEFITS

- Non-toxic ..... Safe for children
- Free of food products ..... No risk of potential allergens
- Re-usable ..... Minimize waste
- Removable ..... Excellent for temporary mounting
- Eliminates producing holes in walls ..... Helps eliminates wall repair
- Will not dry out ..... Long-lasting

### RECOMMENDED FOR

- Bonding items to most smooth surfaces, including blackboards, wood, plaster, brick, glass, tile metal, Formica, porcelain, linoleum and concrete.
- Hanging children's artwork on the refrigerator, stick memos to the phone, stick recipes, party decorations and greeting cards to the wall.
- Stopping vibrations of rattling windows, secure candlesticks, paper tablecloths, shelf paper and drawer linings, secure desk blotters and accessories.

### LIMITATIONS

#### DO NOT USE FOR:

- Hanging heavy objects, such as mirrors and framed pictures
- Sticking items to flocked or paper wall coverings, on peeling or newly painted surfaces.
- Mounting costly artwork and posters
- Exterior applications

### TECHNICAL DATA

Typical Physical Properties		Typical Application Properties	
<b>Color:</b>	Blue	<b>Odor:</b>	Minimal
<b>Appearance:</b>	Putty	<b>Specifications:</b>	Conforms to ASTM D4236
<b>Base:</b>	Synthetic rubber	<b>Application Temperature:</b>	For best performance use and maintain at room temperature

## DIRECTIONS

### Preparation:

Surfaces must be clean and dry.

### Application:

Tear off enough Loctite® Mounting Putty for the job and knead the putty into a soft ball. Place small amount between the surfaces to be fastened and press. **IMPORTANT:** When using Mounting Putty Tabs, use 4 tabs per 1 lb. of weight.

**IMPORTANT:** Test first on absorbent surfaces. If uncertain, test in an inconspicuous area for 24 hours. May leave oily stain on some papers and flat painted surfaces. To remove gently peel away items from mounting surface. Do not pull the putty off painted wall surface. Should any particles remain, simply roll more Fun-Tak over area until clean.

### Clean-up:

To remove any excess putty residue, roll additional mounting putty over the surface area to pick up any remaining particles. Dry cleaning fluid may assist removal of oily stains.

## STORAGE & DISPOSAL

**Not damaged by freezing.** Dispose of unwanted putty with trash.

## LABEL PRECAUTIONS

**Children under 6 years of age should be supervised**  
**Refer to the Safety Data Sheet (SDS) for further information.**

## DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



### Trusted Performance. Proven Results.

For over 50 years, Loctite Brand adhesives and sealants have taken on the toughest jobs. Used in race cars, airplanes, and even in the space-shuttle, Loctite provides solutions for the most demanding industrial, professional and consumer applications. Loctite gives you not the specialization, power and performance to not only get your job done, but to get it done right.

**For Technical Assistance call : 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET**  
[www.loctiteproducts.com](http://www.loctiteproducts.com)



Loctite Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067  
[www.henkelna.com](http://www.henkelna.com)