

Technical Data Sheet

Technical Data Sheet
Revision: 1
Issued: 14.01.2013
Number of pages: 3

Pattex Mounting Strips Removal Strips 2kg & Permanent Strips 3kg

Description:

Double- sided foam mounting strips for removable mounting or permanent mounting applications.

Characteristics:

Pattex NMN Mounting 2kg Strips Removable is a double-sided die cut pad for removable mounting applications for interior and exterior use with excellent UV resistance.

Pattex NMN Permanent 3kg Mounting Strips is a double-sided mounting strip with high holding power and high adhesion. Pattex NMN Permanent Mounting Strip has high initial tack and designed specifically for the most indoor and outdoor usage.

- Easy – without additional tools
- Quite – without drill or drill noise
- Clean – without dirt and dust

APPLICATION FIELD:

- Pattex Mounting Strips can be used to fix objects on many different smooth surfaces like tiles, metal, wood, stone and many plastics* *not for the use on PE, PP, PTFE (Teflon)
- For inside and outside applications.
- Ideal for mounting applications of kitchen and bathroom accessories, household appliances, decoration objects, skirting boards, house numbers, etc.
- Not recommended for applications on delicate surfaces like Silikon, Wall Paper (Vinyl or Paper), not load-bearing or dirt-repellent surfaces

INSTRUCTIONS FOR USE

Application:

- Ensure surfaces to be bonded are clean and free of dust, grease or oil. Surfaces should be load-bearing (Clean surface with alcohol, cleaning benzene or acetone).





Excellence is our Passion

- Apply tape without any air-bubbles on the substrate and remove protection liner and press it afterwards hard on the ground where to bond.
- Avoid application temperatures under 10 °C. Maximum holding power of 2,0kg per strip or 3,0kg (depending on what you are using*) will be reached under ideal conditions: mounting of flat objects (thickness <10mm) to smooth glass or metal surfaces. Direct contact with water can reduce holding power. Final strength is reached after 24h.
- For mounting of objects with a thickness >10mm, holding power per strip is reduced.
 - To fix larger objects (thickness >10mm, weight >2kg) use more strips for removal 2kg strip variant.
 - For 3kg permanent strips, To fix larger objects (thickness >10mm, weight >3kg) use more strips for permanent 3kg strip variant.
- Distribute the strips homogeneous on the surface respecting a space of 3 - 5 cm between each strip.
- On surfaces other than glass or metal, holding power per strip can be reduced.
- Ensure surfaces to be bonded are clean and free of dust, grease or oil. Surfaces should be load bearing (Clean surface with alcohol, cleaning benzene or acetone).

How to Remove the 2kg Strips :

- Give the object a short, sharp turn (take care if removing breakable items such as glass, porcelain, china, etc.) or split the foam carrier with a thread.
- After removing the object, remaining foam can be easily peeled off.

TECHNICAL DATA:

▪ **Removable Mounting Strips 2kg x 12**

Colour / Appearance	White foam / double-sided tape
Carrier material	Polyethylene foam
Adhesive	Acrylic
Liner	Yellow Polyethylene/Propylene
Width	20mm
Length	40mm
Gap bridging capacity	Max. 1,0mm
Temperature resistance	Up to 95°C (short term)
Processing temperature	10°C to 35°C
Shelf life	24 months

▪ **Permanent Mounting Strips 3kg x 12**

Colour / Appearance	White foam / double-sided tape
Carrier material	Polyethylene foam
Adhesive	Synthetic rubber
Liner	Red Polyethylene/Propylene
Width	20mm
Length	40mm
Gap bridging capacity	Max. 1,0mm
Temperature resistance	Up to -40°C to +95°C (short term)
Processing temperature	10°C to 35°C
Shelf life	24 months

Storage:

Store in a dry, dust free place between 10 C° and 30 °C.

Important Remarks:

- Delicate surfaces can be damaged when removing the tape.
- Pattex Mounting Strips is not recommended for the use of silicon.
- Wallpaper (vinyl or paper) not load-bearing or dirt-repellent surfaces.
- In doubt the tape must be tested in an inconspicuous place.

Disposal: Household waste

Pack sizes available

- Removable Mounting Strips 2kg x 12
- Permanent Mounting Strips 3kg x 12

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

Henkel South Africa (Pty) Ltd

22 Skeen Boulevard, Bedfordview, 2007

Toll Free Number: 0800 13 81 81

Website: www.pattex.co.za