WRB

OSI BUTYL FLASH OR OSI ACCEPTED FLASHING MEMBRANE APPLIED OVER WALL SHEATHING AND HEAD JAMB

OSI BUTYL FLASH OR OSI ACCEPTED FLASHING MEMBRANE APPLIED OVER RIGID HEAD FLASHING

OSI QUAD MAX WITH BACKER ROD APPLIED AS PERIMETER SEAL BETWEEN WINDOW FRAME AND ROUGH FRAME

RIGID HEAD FLASHING OR DRIP CAP.

OSI QUAD FOAM APPLIED AS AIR AND MOISTURE BARRIER BETWEEN WINDOW FRAME AND ROUGH HEAD JAMB

OSI QUAD MAX APPLIED AS A BEDDING SEALANT BETWEEN BOTTOM AND UP-TURNED LEG OF RIGID HEAD FLASHING

BLOCK FRAME WINDOW

OSI QUAD FOAM APPLIED AND AIR AND MOISTURE BARRIER BETWEEN WINDOW FRAME AND ROUGH SILL.. FOR LARGER GAPS BACKER ROD IS RECOMMENDED TO MAINTAIN A GAP BETWEEN WINDOW FLANGE AND FOAM

OSI BUTYL FLASH OR OSI ACCEPTED FLASHING MEMBRANE APPLIED AS SILL FLASHING